



UL Online Certifications Directory

[Home](#) [Quick Guide](#) [Contact Us](#) [UL.com](#)

UVAV.S3078 Visual Signaling Appliances for Fire Protective Signaling Systems

[Page Bottom](#)

Visual-signal Appliances for Fire-protective Signaling Systems

[See General Information for Visual-signal Appliances for Fire-protective Signaling Systems](#)

COOPER WHEELOCK INC

S3078

273 BRANCHPORT AVE

LONG BRANCH, NJ 07740-6830 USA

Horn/strobe cover, Model EWR.

Horn/strobe/speaker damage stopper, Part No. EWR.

Strobe light, synchronous type, Model RSSR, followed by -2415C, -2415W, -2475C, -2475W, -24110C, -24110W. For indoor use.

Strobe light, C, H or no letter (to designate lens orientation), followed by a W, R, A, B or G designating lens color (W=White, R=Red, A=Amber, B=Blue, G=Green), followed by S or H for strobe intensity (S = 1.5cd/12,000cp, H = 15cd/70,000cp) which may or may not be followed by 1, 2, 3 (for mounting plate), followed with letter T for termination and by -12, -24, or -115 indicating voltage (12=12VDC, 24=18-31VDC), may be followed by any two alpha/numeric characters indicating lens Lettering and product color. Models with mounting plate designation as 3 can be used outdoors when employing WBB back box.

Strobe covers, Models EN4, EWP.

Strobe damage stopper, Part No. EWP. Intended for visual applications only.

Strobe/Horn, Model AMT followed by no suffix or 4, followed by 12 or 24, followed by WH or WM, followed by any three alpha/numeric characters indicating lens orientation, lens lettering and product color, may or may not be followed by NYC. Suitable for outdoor use.

Strobe light, synchronous type, Model RSSR followed by -24100C (ceiling or wall mount, 15 cd) or -24110W (wall mount, 15 cd). Intended for indoor use.

Strobe/speakers, Models E-70 or -90 followed by WH, WS or WM, followed by 12/24 or 115, followed by up to three alpha/numeric suffixes indicating lens orientation, lens lettering and product cover. Example Model Code: E-70-WM-24-HFR.

Accessories, Models AP, BB, DB, DFB, FBB, FP, FSB1, IOB, RP, SB, SBB, SBL, SBL-1, -2, SFP, UFP, WBB.

Trademark and/or Tradename: "Wheelock", "Cooper Notification"

[Last Updated](#) on 2012-06-29

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".