

DCN-FMIC Flush Microphone Connection Panel



- Stylish and modern design (IF award)
- ► Channel selector output level control

The Microphone Connection Panel connects the pluggable microphone DCN-MICS and DCN-MICL to one of the audio inputs to the Dual Delegate Interface (DCN-DDI).

The Microphone Connection Panel also has an output which controls the output level of the channel selector. This means that when the microphone is active, the output level of the channel selector is reduced to prevent acoustic feedback.

Functions

Interconnections

- 2 m (78.7 in) cable terminated with eight-pole 262° DINtype plug
- Connector to control output level reduction of the channel selector (AMP173977-2 socket)

Technical Specifications

Mechanical	
Mounting	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with DCN-FCOUP couplings and DCN-FEC end caps in any surrounding
Dimensions (H x W x D)	40 x 50 x 50 mm (1.57 x 1.97 x 1.97 in)
Weight	10 g (0.02 lb)
Color	
DCN-FMIC	Silver (RAL 9022)

Ordering Information

DCN-FMIC Flush Microphone Connection	DCN-FMIC
Panel	
flush mounted, silver, microphone to be or-	
dered separately	

Americas:
Bosch Communications Systems
12000 Portland Avenue South
Burnsville, Minnesota, 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschcommunications.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by