

ICP-CP508LW LCD Icon Codepad

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Single key arming of alarm system
- ▶ Fire, medical and panic alarms
- ▶ Easy to use
- ▶ White backlight illuminates keys during day or night

The ICP-CP508LW is an eight-zone LCD codepad for use with certain Solution Series control panels. It has a protective door and a white backlight. Easy to recognize icons display system conditions in a simple to view format. Zone status is indicated numerically across the top of the screen.

The codepad notifies users when there is an alarm and when a zone is opened.

Also included are a number of single button functions that allow a user to perform various system operations by simply holding down a button for 2 sec. For example, holding the [#AWAY key arms the system, holding the [1] key tests the sirens, and holding the [3] key tests the strobe lights.

Functions

Arming Methods

You can arm the system by entering your User code and pressing the [#AWAY] key, or quick arm the system by holding down the [#AWAY] key for 2 sec.

Fire, Medical and Panic Alarms

If programmed to do so, simultaneously pressing the outside buttons of a row on any codepad triggers an audible alarm, and an alarm report is sent to the control panel. Press [4] and [6] simultaneously for a

fire alarm; press [7] and [9] simultaneously for a medical alarm; and press [1] and [3] or [*STAY] and [#AWAY] simultaneously for a panic alarm.

Certifications and approvals

The ICP-CP508LW has been tested to the following standards:

Region	Standards
Australia	A-tick
New Zealand	Tele-permit PTC-200
Europe	CE EMC: EN 55022, EN 55024 Safety: EN 60950 Telecom: TBR21 Environment: EN 50130-4, EN 61000-3-2, EN 61000-3-3

Region	Certification
Europe	CE 2004/108/EC EMC Directive (EMC); 2006/95/EC Low-voltage Directive (LVD) [ICP-CP500PW][ICP-CP508W] [ICP-CP508LW][ICP-CP516LW][ICP-CP516W][ICP-CP500AW]ICP-CP500ALW]

Installation/configuration notes

Compatibility Information Control Panels

ICP-CC404P, ICP-CC408-CHI, ICP-CC408-APR, ICP-CC408P,
ICP-CC408P-ES, ICP-CC488-CHI, ICP-CC488-APR, ICP-CC488P,
ICP-CC488P-ES, CC408, CC488, CC880, Solution 6, Solution 8,
Solution 862, Solution 844, and Solution Ultima 862

Mounting Considerations

The ICP-CP508LW can be wall-mounted indoors using two to four screws.

Parts included

Quant.	Component
1	Codepad

Technical specifications

Enclosure Design

Dimensions:	7.2 cm x 12.7 cm x 2.3 cm (2.8 in. x 5 in. x 1 in.)
-------------	--

Environmental Considerations

Storage Temperature:	+0°C to +50°C (+32°F to 122°F)
Relative Humidity:	20% to 90% (non-condensing)
Radio Frequency Interference (RFI):	Complies with AS/NZS3548

Power Requirements

Operating Voltage:	11 VDC to 14 VDC
Current Draw:	50 mA (maximum)

Ordering information

ICP-CP508LW LCD Icon Codepad

Eight-zone LCD codepad with easy to recognize system-condition icons and numerically- indicated zone status

Order number **ICP-CP508LW**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com