

LECTUS select



The new LECTUS select line is Mobile Access ready and consists of two different reader variants, one with keypad and one without. Both variants are available in black and white colors, and can be flush-mounted, or surface-mounted if the optional mounting frame is used.

To detect unauthorized disassembly, the readers have a tamper contact.

Since they are equipped with a Bluetooth® Low Energy module, it is possible to use mobile credentials, in addition to physical cards, with the Mobile Access solution by Bosch. This option ensures a seamless access, by using a mobile phone for authentication.

The new LECTUS select readers support a range of credential technologies such as MIFARE DESFire EV1, MIFARE DESFire EV2, LEGIC advant, as well as mobile credentials.

The readers have an RS485 interface that uses the OSDP V2 protocol. When operating the reader in this mode, a maximum of eight readers can be connected to the respective controller, the AMC2-4R4CF. The readers address can be set through the four DIP switches. During operation, three LED indicators and a beeper provide clear feedback to the user.

All readers are IP54 rated.

Regulatory information

Region	Regulatory compliance/quality marks
Europe	CE
Global	RoHS

- ▶ Supports Mobile Access
- ▶ Easy installation
- ▶ Sabotage monitoring
- ▶ Three status LED indicators
- ▶ Numbers and symbols backlit

Region	Regulatory compliance/quality marks
USA	FCC

Installation/configuration notes

Compatibility

The readers that support OSDP can be used with BIS (Building Integration System) and AMS (Access Management System) software and support by default the following technologies:

- LEGIC advant
- MIFARE DESFire EV1 and EV2
- Mobile credential (AMS 5.0.1 and above; BIS 5.0.1 and above). For more information on this option, refer to the Datasheet of the Mobile Access available in the online catalog.

Technical specifications

Connectivity

Reader interfaces	RS485
-------------------	-------

Electrical

Operating voltage (VDC)	8 - 30 VDC
Power consumption VAC (VA) (typical - maximum)	3.50 VA

Environmental

Operating temperature (°F)	-13 - 140 °F
----------------------------	--------------

Operating temperature (°C)	-25 - 60 °C
Usage	Indoor; Outdoor
IP rating	IP54

Mechanical

Dimension (H x W x D) (cm)	88 x 101 x 35 cm
Dimension (H x W x D) (in)	3.5 x 4 x 1.4 in
Material	Plastic
Mounting type	Surface-mounted; Flush-mounted
Weight (g)	147.6 g
Weight (lb)	0.33 lb

	ARD-SELECT-BOM, ARD-SELECT-BOKM
Color	Black

	ARD-SELECT-WOM, ARD-SELECT-WOKM
Color	White

Network

Wireless technology standard	Bluetooth® Low Energy
------------------------------	-----------------------

Operation

Audible indication	Yes
Credential type	Cards/keyfobs/tokens; PIN; Mobile credential
Optical indication	LED
Reading format	MIFARE Classic*; MIFARE DESFire EV1; MIFARE DESFire EV2; ISO14443A CSN 32 bit*; LEGIC prime*; LEGIC advant; ISO1593 CSN*
Read range (cm)	<ul style="list-style-type: none"> LEGIC prime: card 65 mm maximum, key fob 40 mm maximum LEGIC advant: card 25 mm maximum, key fob 20 mm maximum

- MIFARE Classic: card 40 mm maximum, key fob 30 mm maximum
- MIFARE DESFire EV1: card 10 mm maximum, key fob 10 mm maximum

Software compatibility	Building Integration System; Access Management System
Wireless transmission frequency	13.56 MHz

	ARD-SELECT-BOKM, ARD-SELECT-WOKM
Keypad	Yes

	ARD-SELECT-BOM, ARD-SELECT-WOM
Keypad	No

System integration

Protocols / standards	OSDP
-----------------------	------

* It is not set by default. Requires specific configuration with OSDP protocol. Ask for more information in advance.

Ordering information

ARD-SELECT-BOM Reader, OSDP, BLE, black

OSDP reader for MIFARE classic, MIFARE EV1 and EV2, LEGIC prime and advant, in black, designed for surface and flush mountings, IP54 rated, with BLE module.
Order number **ARD-SELECT-BOM | F.01U.389.847**

ARD-SELECT-WOM Reader, OSDP, BLE, white

OSDP reader for MIFARE classic, MIFARE EV1 and EV2, LEGIC prime and advant, in white, designed for surface and flush mountings, IP54 rated, with BLE module.
Order number **ARD-SELECT-WOM | F.01U.389.848**

ARD-SELECT-BOKM Reader, OSDP, keypad, BLE, black

OSDP reader for MIFARE classic, MIFARE EV1 and EV2, LEGIC prime and advant, in black, with keypad, designed for surface and flush mountings, IP54 rated, with BLE module.
Order number **ARD-SELECT-BOKM | F.01U.389.851**

ARD-SELECT-WOKM Reader, OSDP, keypad, BLE, white

OSDP reader for MIFARE classic, MIFARE EV1 and EV2, LEGIC prime and advant, in white, with keypad, designed for surface and flush mountings, IP54 rated, with BLE module.
Order number **ARD-SELECT-WOKM | F.01U.389.852**

Accessories

ARA-SELECT-SWA Wallmount Box Lectus Select, silver

Wallmount box for LECTUS select Reader Series, silver, fits to all readers with black front surface.

Order number **ARA-SELECT-SWA | F.01U.389.869**

ARA-SELECT-WWA Wallmount Box Lectus Select, white

Wallmount box for LECTUS select Reader Series, white

Order number **ARA-SELECT-WWA | F.01U.389.868**

Represented by:

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:

Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:

Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com