# FMM-100 Spectrum Family of Die-cast Metal Manual Stations

www.boschsecurity.com





- ► Terminal connections
- ▶ Gold-plated alarm contacts for corrosion resistance
- ► Surface- or flush-mounted back boxes
- ▶ Optional labels

The FMM-100 Spectrum family are versatile, high-quality, metal manual stations in blue or yellow. Designed for special applications such as weather alert, hazmat spills, police call, medical emergencies, door release, and fire suppression. Designers can choose from a wide array of special application labels to designate the function of each pull station. The spectrum series manual stations have two single-pole, double-throw (SPDT) contacts that are individually field-configurable for normally-open (NO) or normally-closed (NC) operation. The manual stations come with a key lock and contain gold-plated contacts to resist corrosion.

#### **Functions**

#### Operation

When the bar on the front of the manual station is pulled, it latches open and is easily visible from 50 ft (15 m). Reset the activation bar by opening the manual station with the key and placing the activation bar in its normal upright position. An optional scored acrylic break rod is available.

## **Certifications and approvals**

Region	Regulatory compliance/quality marks	
USA	UL	UNIU: Boxes, Non-coded (UL38), UNIU7: Boxes, Non-coded Certified for Canada (ULC-S528-M91)

## Installation/configuration notes

### **Compatibility Information**

These manual stations are compatible with all conventional Bosch Security Systems, Inc. control panels.

# **Mounting Considerations**

These manual stations can be surface mounted on the FMM-100BB Series Surface-mount Back Boxes or flush mounted on a standard single-gang back box. Mounting locations are subject to local regulations. To comply with ADA standards, the manual station must be less than 48 in. (1.2 m) above the floor for front wheelchair access and less than 54 in. (1.3 m) above the floor for side wheelchair access.



#### WARNING

This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov.

Labels for Top

Blue	Yellow
•	•
•	•
•	
Blue	Yellow
	•
•	•
•	
	•
	•
	•
•	
•	
	•
	•
•	•

## **Technical specifications**

## **Environmental**

Relative Humidity:	90% at +100°F (+38°C)
Temperature (operating):	-40°F to +150°F (-40°C to +66°C)

#### Mechanical

Dimensions (H x W x D):	4.75 in. x 3.25 in. x 1.1 in. (12 cm x 8.3 cm x 2.8 cm)
Material:	Die-cast metal

#### Inputs

Switch Rating:	1 A at 30 VDC or 125 VAC
----------------	--------------------------

#### **Trademarks**

All hardware/software product names used in this document are likely to be registered trademarks and must be treated accordingly.

## **Ordering information**

# FMM-100SAT2CK-B Manual station, single-action, blue

Versatile, high-quality, single-action metal manual station in blue with key lock and gold-plated contacts Order number FMM-100SAT2CK-B

# FMM-100SAT2CK-Y Manual station, single-action, yellow

Versatile, high-quality, single-action metal manual station in yellow with key lock and gold-plated contacts

Order number FMM-100SAT2CK-Y

# FMM-100DAT2CK-B Manual station, double-action, blue

High-quality, metal manual emergency station in blue Order number FMM-100DAT2CK-B

#### Accessories

# FMM-100BB-Y Surface backbox, 4.74x3.25x2.25", yellow

Yellow cast-metal back box Order number FMM-100BB-Y

#### D102 Replacement key for D101 lock set

The D102 is a replacement key for locks stamped with 1358.

Order number **D102** 

# FMM-100BB-B Surface backbox, 4.74x3.25x2.25", blue

Blue cast-metal back box Order number **FMM-100BB-B** 

#### Represented by:

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 emea.securitysystems@bosch.com emea.boschsecurity.com Germany: Bosch Sicherheitssysteme GmbH Robert-Bosch-Ring 5 85630 Grasbrunn Germany www.boschsecurity.com North America: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 onlinehelp@us.bosch.com www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia